







TECHNICAL DATA SHEET - OAK COLLECTION




OAK THREE
BQO 306 SMOKED WHITE



001 PRODUCT DESCRIPTION

| | | |
|---|--------------|-----------------------------------|
|  | Wood type | European Oak |
|  | Grading | Select/Bis, Elegance or Classic |
|  | Core/backing | Multilayer: pine and poplar |
|  | Coating | Reactive stains and pigmented oil |
|  | Texture | Smooth |
|  | Bevel | Micro V, 2 side |


002 DIMENSIONS

| | | Straight | Hungarian point chevron | | | Herringbone | |
|---|-----------------------|----------------------------|--------------------------------|-----------------------------|-----------------------------|----------------------------|-----------------------------|
|  | Thickness/ surface | 35/64" - 1/8" (14/3 mm) | 35/64" - 1/8" (14/3 mm) | 19/32" - 5/32" (15/4 mm) | 19/32" - 5/32" (15/4 mm) | 35/64" - 1/8" (14/3 mm) | 19/32" - 5/32" (15/4 mm) |
|  | Width | 7 31/64" (190 mm) | 4 23/32" (120 mm) | 3 35/64" (90 mm) | 5 33/64" (140 mm) | 3 35/64" (90 mm) | 5 33/64" (140 mm) |
|  | Length | 74 51/64" (1900 mm) | 23 5/8" (600 mm) | 15 3/4" (400 mm) | 27 9/16" (700 mm) | 20 5/64" (510 mm) | 25 63/64" (660 mm) |

003 TECHNICAL PERFORMANCE

| | | |
|---|-----------------------------|--|
|  | Norm | En 14342 |
|  | FSC | CU-COC-874752 |
|  | Formaldehyde emission class | Carb2 |
|  | Flammability class | Dfl-s1 |
|  | Underfloor heating | Yes - Warranty certificate available  |
|  | Floor cooling | Yes - Warranty certificate available  |
|  | Thermal conductivity | 0.17 W/mK |
|  | Moisture content | 7 % (+/- 2%) |
|  | Advisory use | Suitable for: residential, commercial, Hospitality, Retail |

004 ADDITIONAL INFORMATION

| | | |
|---|--------------|------------------------|
|  | Installation | Glued down |
|  | Jointing | Tongue and groove |
|  | Sanding | Yes (1 mm per sanding) |




SELECT / BIS

Knots: minimal

Cracks: none

Sapwood: limited




ELEGANCE

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited



CLASSIC

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited

