







TECHNICAL DATA SHEET - OAK COLLECTION




OAK THREE
BQO 309 INTENSE TERRA



001 PRODUCT DESCRIPTION

	Wood type	European Oak
	Grading	Select/Bis, Elegance or Classic
	Core/backing	Multilayer: pine and poplar
	Coating	Reactive stains and pigmented oil
	Texture	Smooth
	Bevel	Micro V, 2 side


002 DIMENSIONS

		Straight	Hungarian point chevron			Herringbone	
	Thickness/ surface	35/64" - 1/8" (14/3 mm)	35/64" - 1/8" (14/3 mm)	19/32" - 5/32" (15/4 mm)	19/32" - 5/32" (15/4 mm)	35/64" - 1/8" (14/3 mm)	19/32" - 5/32" (15/4 mm)
	Width	7 31/64" (190 mm)	4 23/32" (120 mm)	3 35/64" (90 mm)	5 33/64" (140 mm)	3 35/64" (90 mm)	5 33/64" (140 mm)
	Length	74 51/64" (1900 mm)	23 5/8" (600 mm)	15 3/4" (400 mm)	27 9/16" (700 mm)	20 5/64" (510 mm)	25 63/64" (660 mm)

003 TECHNICAL PERFORMANCE

	Norm	En 14342
	FSC	CU-COC-874752
	Formaldehyde emission class	Carb2
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail

004 ADDITIONAL INFORMATION

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)




SELECT / BIS

Knots: minimal

Cracks: none

Sapwood: limited




ELEGANCE

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited



CLASSIC

Knots: unlimited/filled

Cracks: allowed

Sapwood: limited

